

# Mortises/ Latches



**AM9100** UL & ULC listed for high traffic commercial, institutional and industrial uses where durability and security are of the greatest concern. **Standard features:** **TECH SPECS** GRADE: ANSI grade 1 **CASE:** Heavy Gauge, Plated Steel **ARMOR FRONT:** Heavy gauge stainless steel. Adjustable bevel **LATCH BOLT:** Brass-Anti friction type, 3/4" throw **FACEPLATE:** 1 1/4" stainless steel (1" available) **DEADBOLT:** Brass-with hardened steel inserts, 1" throw **STRIKE:** 4 7/8" ASA (1 1/4" lip to center standard, various sizes available upon request) **HUB:** 8mm square **THUMB TURN HUB:** 3/16" (5mm) on the diamond **DISTANCE:** Hub to cylinder: 3 5/8" c to c Hub to thumbturn: 2 7/16" c to c **DUST BOX:** Brass, stainless steel or US10 **BACKSET:** 70MM **CYLINDER:** Accepts 15/32" diameter threaded round mortise cylinder (C series) **UL-LISTED:** All locks are UL-listed for 3 hours UL label stamped on front (ULC available) UL sticker on case **Available trims:** Rose and Backplates: SIG200-203-243-244-245 Cylinder Collar: SIG203C and C collar Thumbturn: SIG250-255-260-265

[Learn More](#)



**EU1000** **Applications:** For Heavy duty residential doors: Single and multifamily housing. For use with levers only. Lock function for use with P series profile Cylinders. Euro Teste and approved for CE-EN12209

**Standard features:** **Handing:** Field reversible **Case:** Closed black painted **Faceplate:** Removable stainless steel or solid brass 20 x 235mm with square corners (standard) 24 x 235mm square or radius 20 x 235mm radius 18 x 235mm square or radius **Latch bolt:** Zinc Plated **Deadbolt:** Double Throw **Backset:** 50mm, 60mm and 70mm **Hub:** 8mm square

**Stock Functions**

	50mm	60 mm	70 mm
Passage	EU1525	EU1625	EU1725
Lock	EU1556	EU1656	EU1756
Privacy	EU1561	EU1661	EU1761

[Click here for 50mm backset template](#) [Click here for 60mm backset template](#) [Click here for 70mm backset template](#)

[Learn More](#)



**EU2000** EU2000 Narrow-style European mortise lock **Applications** For heavy duty commercial and residential doors. For use with levers only. Lock function for use with P Series profile cylinders. **Standard Features** **Case:** High graded steel **Faceplate:** Stainless steel or solid brass 24 x 245mm with square corners **Latch bolt:** Zinc/Nickel-plated **Handing:** Field Reversible **Dead bolt:** Die cast, zinc/Nickel plated **Backset:** 25mm, 30mm, 35mm, 40mm and 45mm **Distances:** Hub to cylinder: 92mm c.to c. **Hub:** 8mm square

**Stock Functions**

	25mm	30 mm	35 mm	40 mm	45 mm
Passage	EU2025	EU2025	EU2025	EU2025	EU2025
Lock	EU2056	EU2056	EU2056	EU2056	EU2056
Privacy	EU2061	EU2061	EU2061	EU2061	EU2061

[Click here for 50mm backset template](#) [Click here for 60mm backset template](#) [Click here for 70mm backset template](#)

[Learn More](#)